Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard 29CFR 1910. 1200. Standard must be consulted for specific requirements.					GENUINE JOE ALL PURPOSE CLEANER QUICK IDENTIFIER Common Name: (Used on label)				
								<u>-</u>	
SECTION 1 - MANUFACTURER'S INFORMATION									
Manufacturer's Name: Address: City, State, Zip: Signature of Preparer:	r, State, Zip: Charlotte, NC 28208 Other Calls:			1-800-255-3924 (CHEMTEL) 1-704-398-0487 2/24/2009				_	
SECTION 2 - HAZARD	OUS INGRE	DIENTS / IDENTITY							
Hazardous Component	OSHA PEL	ACGIH PEL	Other Exposure Limits	Percent by wt. (Optional)	CAS Number				
2-BUTOXYETHANOL				25 PPM	25 PPM		1.2 - 1.5	111-76-2	
SECTION 3 - PHYSICA	AL AND CHE	MICAL CHARACTERIST	rics						
Boiling Point: 212 DEG F Specific Gravity (H2O=1): 1.00 Vapor Pressure (mm Hg): NE Vapor Density (Air=1): NE PH, as is: 11.5 - 12.5 Melting Point: NA Solubility in Water: COMPLETE Reactivity in Water: NONE Apperance & Odor: CLEAR, LIGHT				YELLOW LIQUID WITH CITRUS ODOR					
SECTION 4 - FIRE & E	XPLOSION I	DATA							
Flash Point: NA Flammable Limits in Air Auto Ignition Temp.: N. Extinguishing Media: F Special Fire Fighting Pr	A OAM, DRY C	CHEMICAL, CARBON DI			SE WATER S	PRAY TO KEEP CO	NTAINERS COO	L.	
Unusual Fire & Explosion		NONE Flammability - 0, Reactiv	vity - 0						
SECTION 5 - PHYSICA	AL HAZARDS	(REACTIVITY DATA)							
Stability:	Unstable Stable	X	Conditions to Avoid:	EXCESSIVE	HEAT, SPAR	KS AND OPEN FLA	ME.		
Incompatibilty (Materials	s to Avoid):	STRONG OXIDIZERS	AND REDUCING AGI	ENTS (ACIDS	AND BASES))			
Hazardous Decomposit	ion Products:	: THERMAL DE	COMPOSITION MAY	PRODUCE O	XIDES OF CA	RBON			
Hazardous Polymerization:		May Occur Will Not OccurX	Conditions to Avoid: NONE						

NA - Not Applicable NE - Not Established

PAGE 1 OF 2