intelliFAX®-4750E Laser Fax, Phone & Copier



The intelliFAX®-4750E. Laser fax for your business needs.



 Time saving, full-featured 33.6 kbps fax capability with 232-station auto-dialing, and 600-page* out-of-paper memory capacity.

PHONE

 Convenience and functionality are provided with built-in telephone handset.

COPY

 Versatile copy capability allowing plain-paper copying with options such reduction and enlargement from 50% to 200% and sorting.





intelliFAX®-4750E Laser Fax, Phone & Copier

Robust and efficient.

Simple to use, with advanced functions

This high speed, business class laser fax with a Super G3 33.6 Kbps modem has a high monthly duty cycle and high yield consumables to handle demanding business applications. It includes Dual Access as well as QuickScar®, which lets you scan faxes into memory while sending or receiving. 8 MB of memory stores up to 600 pages* for out-of-paper reception. The intelliFax®-4750E is also compatible with caller ID** and distinctive ring** to better blend in with your workflow. All this and more with fast laser performance and reliability at low operating costs.

A full featured fax machine

At the heart of this fax machine is a professional plain paper fax facility with advanced business functions. The intelliFAX®-4750E has a 250-sheet input tray and 600-page* out-of-paper memory so you won't miss faxes. It is able to forward received and stored faxes to another fax machine as well as page you if a fax is received. You can even retrieve your faxes from it remotely.

Increase your efficiency

Spend less time faxing out documents with features such as a 50-page Auto Document Feeder (ADF), fax broadcasting to up to 282 locations, buttons and 232-speed dial locations. You can group preprogrammed fax numbers and send a fax to selected groups automatically.

Service and support are part of the package

We are dedicated to comprehensive service and support. We provide a one-year limited warranty backed by our nationwide network of authorized customer-care centres. We also provide machine lifetime toll-free technical support to help you get the most out of your fax.

For added support, the "Brother Solutions Center" (http://solutions.brother.com) is

an online repository of information, driver downloads, user manuals and FAQs to help you get the most out of your intelliFax®-4750E.









PRODUCT SPECIFICATIONS

FA)

- Modem speed/ best transmit speed* 33.6 Kbps/2 sec.
- Auto document feed capacity 50 pages
- Paper capacity 250 sheets
- Memory capacity (max. pages)*
 8 MB (600 pages)
- Broadcasting (# of locations) 282 locations
- One touch/ speed dial locations 32/200
- Group dial Yes (up to 6)
- Quickscan[®] (seconds/page)* Approx. 2 sec.

- Remote retrieval Yes
- Fax forwarding/paging Yes/Yes
- Fax compatibility Super G3
- Coding methods MH/MR/MMR/JBIG
- Recording paper size Letter/legal
- Document scan width 8.15"
- Fax resolution standard 203 x 98 lines/inch
- Fax resolution fine 203 x 196 lines/inch
- Fax resolution super fine 203 x 392 lines/inch
- Grayscale 64
- Delayed transmission/polling Yes/Yes

TELEPHONE

- Dialing system Selectable pulse/tone
- Telephone handset Yes
- Speakerphone Monitor only
- Caller ID**/ distinctive ring ready** Yes/Yes

COPY

- B&W copying
- Copies per minute (cpm) Up to 15
- Copy resolution (dpi) 600 dpi class
- Multi-copying/sort Up to 99/Yes
- Reduction/enlargement 50%-200%

OTHER_

- Yield of included starter print cartridge Approximately 3,000 pages
- Carton dimensions (W x D x H) 516 mm x 561 mm x 460 mm
- Unit dimensions
 (W x D x H)
 435 mm x 442 mm x 323 mm
- Unit/carton weight 12 kg/16.5 kg
- UPC code 0 1250 260 2835
- Approved cUL and ISC



OPTIONAL SUPPLIES AND ACCESSORIES[†]

- Item
 Drum unit
 Toner cartridge
 Toner cartridge
 Lower tray
 10/100 Base TX Ethernet Network
 Print/Fax Server
- Part Number DR-400 (appro
- DR-400 (approx. 20,000 pages) DR-430 (approx. 3,000 pages) ▲ TN-460 (approx. 6,000 pages) ▲ LT-400

NC-8100H

For more information please call 1-877-BROTHER (1-877-276-8437) or visit our web site: www.brother.ca



