

destroyit®

BUSINESS SHREDDERS

→ 2360 DESKSIDE SHREDDER

“SPS” (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; “Easy Switch” control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bag is full or when cabinet door is opened; double protection against overheating; “ESM” (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | high quality, hardened steel cutting shafts take staples, paper clips, and credit cards (strip- and cross-cut models) | super micro-cut (SMC) model meets all NSA/CSS specifications and is DOD approved | lifetime warranty on the cutting shafts (strip- and cross-cut models) | 1 year warranty on SMC cutting shafts | quiet and powerful single phase motor | durable gears enclosed in dust-proof housing | high quality wooden cabinet mounted on casters | environmentally friendly reusable plastic bag | 13 gallon shred volume

Dimensions (D x W x H): 11 ¾ x 15 ½ x 28 ¾ inches, Shipping weight: 53 lbs.



EASY SWITCH



Oversized, multifunction control element uses integrated optics to indicate operational status.

ELECTRONIC SAFETY SHIELD



“SPS” safety features include an electronically controlled safety shield in the feed opening.

→ 2360 STRIP-CUT

| | |
|-----------------|-----------------|
| Strip width | 3/16" (4 mm) |
| Sheet capacity | 12-14* |
| Security level | 2 |
| Feed opening | 9 ½" |
| Max. horsepower | 1/2 |

→ 2360 CROSS-CUT

| | |
|-----------------|-----------------------------|
| Particle size | 3/32" x 5/8" (2 x 15 mm) |
| Sheet capacity | 6-8* |
| Security level | 4 |
| Feed opening | 9 ½" |
| Max. horsepower | 1/2 |

→ 2360 SMC HIGH SECURITY

| | |
|-----------------|------------------------------|
| Particle size | 1/32" x 3/16" (.8 x 5 mm) |
| Sheet capacity | 5-7* |
| Security level | 6 |
| Feed opening | 9 ½" |
| Max. horsepower | 1/2 |

* may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 3/2011.

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com